EKI-7659CPI

8+2G Combo Ports Industrial PoE Managed Redundant Gigabit Ethernet Switch

User Manual

Copyright

The documentation and the software included with this product are copyrighted 2007 by Advantech Co., Ltd. All rights are reserved. Advantech Co., Ltd. reserves the right to make improvements in the products described in this manual at any time without notice. No part of this manual may be reproduced, copied, translated or transmitted in any form or by any means without the prior written permission of Advantech Co., Ltd. Information provided in this manual is intended to be accurate and reliable. However, Advantech Co., Ltd. assumes no responsibility for its use, nor for any infringements of the rights of third parties, which may result from its use.

Acknowledgements

Intel and Pentium are trademarks of Intel Corporation.
Microsoft Windows and MS-DOS are registered trademarks of Microsoft Corp.
All other product names or trademarks are properties of their respective owners.

Part No.
Printed in China

3th Edition
October 2009

Product Warranty (2 years)

Advantech warrants to you, the original purchaser, that each of its products will be free from defects in materials and workmanship for two years from the date of purchase.

This warranty does not apply to any products which have been repaired or altered by persons other than repair personnel authorized by Advantech, or which have been subject to misuse, abuse, accident or improper installation. Advantech assumes no liability under the terms of this warranty as a consequence of such events.

Because of Advantech′s high quality-control standards and rigorous testing, most of our customers never need to use our repair service. If an Advantech product is defective, it will be repaired or replaced at no charge during the warranty period. For out-of-warranty repairs, you will be billed according to the cost of replacement materials, service time and freight. Please consult your dealer for more details.

If you think you have a defective product, follow these steps:

1. Collect all the information about the problem encountered. (For example, CPU speed, Advantech products used, other hardware and software used, etc.) Note anything abnormal and list any onscreen messages you get when the problem occurs.
2. Call your dealer and describe the problem. Please have your manual, product, and any helpful information readily available.
3. If your product is diagnosed as defective, obtain an RMA (return merchandize authorization) number from your dealer. This allows us to process your return more quickly.
4. Carefully pack the defective product, a fully-completed Repair and Replacement Order Card and a photocopy proof of purchase date (such as your sales receipt) in a shippable container. A product returned without proof of the purchase date is not eligible for warranty service.
5. Write the RMA number visibly on the outside of the package and ship it prepaid to your dealer.

Declaration of Conformity

CE

This product has passed the CE test for environmental specifications. Test conditions for passing included the equipment being operated within an industrial enclosure. In order to protect the product from being damaged by ESD (Electrostatic Discharge) and EMI leakage, we strongly recommend the use of CE-compliant industrial enclosure products.

FCC Class A

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

Technical Support and Assistance

Step 1. Visit the Advantech web site at **www.advantech.com/support** where you can find the latest information about the product.

Step 2. Contact your distributor, sales representative, or Advantech's customer service center for technical support if you need additional assistance. Please have the following information ready before you call:
- Product name and serial number
- Description of your peripheral attachments
- Description of your software (operating system, version, application software, etc.)
- A complete description of the problem
- The exact wording of any error messages

Safety Instructions

1. Read these safety instructions carefully.
2. Keep this User's Manual for later reference.
3. Disconnect this equipment from any AC outlet before cleaning. Use a damp cloth. Do not use liquid or spray detergents for cleaning.
4. For plug-in equipment, the power outlet socket must be located near the equipment and must be easily accessible.
5. Keep this equipment away from humidity.
6. Put this equipment on a reliable surface during installation. Dropping it or letting it fall may cause damage.
7. The openings on the enclosure are for air convection. Protect the equipment from overheating. DO NOT COVER THE OPENINGS.
8. Make sure the voltage of the power source is correct before connecting the equipment to the power outlet.
9. Position the power cord so that people cannot step on it. Do not place anything over the power cord.
10. All cautions and warnings on the equipment should be noted.
11. If the equipment is not used for a long time, disconnect it from the power source to avoid damage by transient overvoltage.
12. Never pour any liquid into an opening. This may cause fire or electrical shock.
13. Never open the equipment. For safety reasons, the equipment should be opened only by qualified service personnel.
14. If one of the following situations arises, get the equipment checked by service personnel:
    a. The power cord or plug is damaged.
    b. Liquid has penetrated into the equipment.
    c. The equipment has been exposed to moisture.
    d. The equipment does not work well, or you cannot get it to work according to the user's manual.
    e. The equipment has been dropped and damaged.
    f. The equipment has obvious signs of breakage.

15. DO NOT LEAVE THIS EQUIPMENT IN AN ENVIRONMENT WHERE THE STORAGE TEMPERATURE MAY GO BELOW -40℃ (-40℉) OR ABOVE 85℃ (185℉). THIS COULD DAMAGE THE EQUIPMENT. THE EQUIPMENT SHOULD BE IN A CONTROLLED ENVIRONMENT.

Safety Precaution - Static Electricity

Follow these simple precautions to protect yourself from harm and the products from damage.

1. To avoid electrical shock, always disconnect the power from your PC chassis before you work on it. Don't touch any components on the CPU card or other cards while the PC is on.
2. Disconnect power before making any configuration changes. The sudden rush of power as you connect a jumper or install a card may damage sensitive electronic components.

Contents

Chapter 1 Overview 2

1.1 Introduction 2
1.1.1 The SFP Advantage 2
1.1.2 Power-over-Ethernet (PoE) 2
1.1.3 High-Speed Transmissions 2
1.1.4 Dual Power Input 2
1.1.5 Flexible Mounting 3
1.1.6 Advanced Protection 3
1.1.7 Wide Operating Temperature 3
1.1.8 Easy Troubleshooting 3
1.2 Features 4
1.3 Specification 5
1.4 Packing List 7
1.5 Safety Precaution 7

Chapter 2 Installation 10

2.1 LED Indicators 10
Table 2.1: EKI-7659CPI LED Definition 10
2.2 Dimensions (units: mm) 12
Figure 2.1: Front View of EKI-7659CPI 12
Figure 2.2: Side View of EKI-7659CPI 13
Figure 2.3: Rear View of EKI-7659CPI 14
Figure 2.4: Top View of EKI-7659CPI 15
2.3 Mounting 16
2.3.1 Wall mounting 16
Figure 2.5: Combine the Metal Mounting Kit (units: mm) 16
2.3.2 DIN-rail Mounting 17
Figure 2.6: Installation to DIN-rail Step 1 17
Figure 2.7: Installation to DIN-rail Step 2 18
2.4 Network Connection 19
2.5 Connection to a Fiber Optic Network 19
Figure 2.8: Transceiver to the SFP module 19
Figure 2.9: Transceiver Inserted 20
Figure 2.10: LC connector to the transceiver 20
Figure 2.11: Remove LC connector 21
Figure 2.12: Pull out from the transceiver 21
2.6 Power Connection 22
Figure 2.8: Pin Assignment of the Power Connector 22

Chapter 3 Configuration 25

3.1 RS-232 Console 25
Figure 3.1: Open Hyper Terminal 25
Figure 3.2: COM Port Properties Setting 26
Figure 3.3: Login Screen: RS-232 Configuration 26

Figure 3.4: Command Line Interface 27
3.1.1 Commands Level 27
Table 3.1: Command Level 27
3.1.2 Commands Set List..... 28
Table 3.2: Commands Set List 28
3.1.3 System Commands Set 28
Table 3.3: System Commands Set.....28
3.1.4 Port Commands Set..... 29
Table 3.4: Port Commands Set.....29
3.1.5 Trunk Commands Set 30
Table 3.5: Trunk Commands Set.....30
3.1.6 VLAN Commands Set..... 31
Table 3.6: VLAN Commands Set.....31
3.1.7 Spanning Tree Commands Set..... 32
Table 3.7: Spanning Tree Commands Set 32
3.1.8 QOS Commands Set 33
Table 3.8: QOS Commands Set.....33
3.1.9 IGMP Commands Set 33
Table 3.9: QOS Commands Set.....33
3.1.10 Mac/Filter Table Commands Set 33
Table 3.10: Mac/Filter Table Commands Set.....34
3.1.11 SNMP Commands Set..... 34
Table 3.11: SNMP Commands Set.....34
3.1.12 Port Mirroring Commands Set 35
Table 3.12: Port Mirroring Commands Set 35
3.1.13 802.1x Commands Set 35
Table 3.13: 802.1x Commands Set.....35
3.1.14 TFTP Commands Set..... 36
Table 3.14: TFTP Commands Set 36
3.1.15 SystemLog, SMTP and Event..... 36
Table 3.15: SysLog,SMTP,Event Commands Set.....36
3.1.16 SNTP Commands Set 37
Table 3.16: SNTP Commands Set.....37
3.1.17 X-ring Commands Set 38
Table 3.17: X-ring Commands Set.....38
3.1.18 PoE Commands Set 38
Table 3.18: PoE Commands Set.....38
3.2 Web Browser 39
Figure 3.5: Type the address in the URL.....39
Figure 3.6: Web Login Window.....39
Figure 3.7: Main page.....40
3.2.1 System..... 40
Figure 3.8: System Information.....41
Figure 3.9: IP Configuration.....42
Figure 3.10: DHCP Server - System Configuration....43
Figure 3.11: DHCP Server – Client Entries 43
Figure 3.12: DHCP Server – Port and IP Binding.....44

Figure 3.13: TFTP – Update Firmware 44
Figure 3.14: TFTP – Restore Configuration..... 45
Figure 3.15: TFTP – Backup Configuration..... 45
Figure 3.16: Syslog Configuration 46
Figure 3.17: SMTP Configuration..... 47
Figure 3.18: Event Configuration..... 48
Figure 3.19: Fault Relay Alarm..... 49
Table 3.18: UTC Timezone..... 49
Figure 3.20: SNTP Configuration 51
Figure 3.21: IP Security..... 52
Figure 3.22: User Authentication 53
3.2.2 Port..... 54
Figure 3.23: Port Statistics..... 54
Figure 3.24: Port Control..... 55
Figure 3.25: Aggregator Setting 56
Figure 3.26: Aggregator Information 56
Figure 3.27: State Activity..... 57
Figure 3.28: Port Mirroring 58
Figure 3.29: Rate Limiting 59
3.2.3 Protocol 60
Figure 3.30: VLAN Configuration 60
Figure 3.31: Port based mode 61
Figure 3.32: Port based mode-Add interface..... 62
Figure 3.33: 802.1Q VLAN Configuration 63
Figure 3.34: 802.1Q Group Configuration 64
Figure 3.35: 802.1Q Group Configuration-Edit 64
Figure 3.36: RSTP System Configuration interface.... 66
Figure 3.37: RSTP Port Configuration interface 66
Figure 3.38: SNMP System Configuration interface... 67
Figure 3.39: Trap Configuration interface..... 68
Figure 3.40: SNMP V3 configuration interface 69
Figure 3.41: QoS Configuration interface 72
Table 3.19: IGMP types..... 73
Figure 3.42: IGMP Configuration interface 74
Figure 3.43: X-ring Interface..... 75
3.2.4 Security..... 76
Figure 3.44: 802.1x/Radius System Configuration 76
Figure 3.45: 802.1x/Radius - Port Setting interface 77
Figure 3.46: 802.1x/Radius - Misc Configuration..... 78
Figure 3.47: Static MAC Addresses interface 78
Figure 3.48: MAC Filtering interface..... 79
Figure 3.49: All MAC Address interface 79
Figure 3.50: PoE Status 80
Figure 3.51: Factory Default interface 81
Figure 3.52: Save Configuration interface 81
Figure 3.53: System Reboot interface 82
Chapter 4 Troubleshooting 84
Appendix A Pin Assignment & Wiring 86
Figure A.1: RJ-45 Pin Assignment..... 86

Figure A.2: EIA/TIA-568B 86
Figure A.3: EIA/TIA-568A 86
Figure A.4: DB 9-pin female connector 87
Appendix B Compatible SFP Modules 90

CHAPTER 1

Overview

Sections include:

- Introduction
- Features
- Specifications
- Packing List
- Safety Precaution

Chapter 1 Overview

1.1 Introduction

To create reliability in your network, the EKI-7659CPI comes equipped with a proprietary redundant network protocol—X-Ring that was developed by Advantech, which provides users with an easy way to establish a redundant Ethernet network with ultra high-speed recovery time less than 10 ms.

Aside from 8 x 10/100Base-TX fast Ethernet ports, the EKI-7659CPI comes equipped with 2 combo 10/100/1000 Mbps RJ-45 copper ports or mini-GBIC expansion ports. Traditional RJ-45 ports can be used for uplinking wide-band paths in short distance (< 100 m), or the appropriate replaceable SFP module can be used for the application of wideband uploading and long distance transmissions to fit the field request flexibility. Also, the long MTBF (Mean Time Between Failures) ensures that the EKI-7659CPI will continue to operate until a Gigabit network infrastructure has been established, without requiring any extra upgrade costs. Besides, the equipment support **48V DC power input** and provides the **PoE function w/ 48V DC output** for kinds of Powered Devices to receive power as well as data over the RJ-45 cable.

1.1.1 The SFP Advantage

The EKI-7659CPI's two SFP fiber slots provide a lot of flexibility when planning and implementing a network. The slots can accept any SFP-type fiber module and these modules are designed for transmitting over distances of either 500m (multi-mode), 10km, 30km, 50km, 70km or 110km (single-mode) – and the slots support SFP modules for WDM single-fiber transmissions. This means that you can easily change the transmission mode and distance of the switch by simply pulling out the SFP module and plugging in a different module. The SFP modules are hot-swappable and plug-and-play! Also, the fact that the switch has two of these slots, means that the network manager can, for example, have one 10km module in one slot and one 110km in the other.

1.1.2 Power-over-Ethernet (PoE)

PoE eliminates the need to run AC power to other devices on a wired LAN. While using Power-over-Ethernet system, installers need to run only a single Category 5 Ethernet cable that carries both power and data to each device. This allows greater flexibility in the locating of network devices and significantly decreasing installation costs in many cases.

1.1.3 High-Speed Transmissions

The EKI-7659CPI includes a switch controller that can automatically sense transmission speeds (10/100 Mbps). The RJ-45 interface can also be auto-detected, so MDI or MDI-X is automatically selected and a crossover cable is not required. All Ethernet ports have memory buffers that support the store-and-forward mechanism. This assures that data is properly transmitted.

1.1.4 Dual Power Input

EKI-7659CPI redundant power input design is with power reserve protection to prevent the switch device broken by wrong power wiring. When one of power input is fail, P-Fail LED will turn on and send an alarm through a relay output for notifying user.

1.1.5 Flexible Mounting

EKI-7659CPI is compact and can be mounted on a DIN-rail or panel, so it is suitable for any space-constrained environment.

1.1.6 Advanced Protection

The power line of EKI-7659CPI supports up to 3,000 V_{DC} EFT protection, which secure equipment against unregulated voltage and make systems safer and more reliable. Meanwhile, 4,000 V_{DC} ESD protections for Ethernet ports make EKI-7659CPI more suitable for harsh environments.

1.1.7 Wide Operating Temperature

The operating temperature of the EKI-7659CPI is between -10 ~ 60 ℃. With such a wide range, you can use the EKI-7659CPI in some of the harshest industrial environments that exist.

1.1.8 Easy Troubleshooting

LED indicators make troubleshooting quick and easy. Each 10/100 Base-TX port has 2 LEDs that display the link status, transmission speed and collision status. Also the three power indicators P1, P2 and P-Fail help you diagnose immediately.

1.2 Features

- 2 Gigabit Copper/SFP combo ports, plus 8 Fast Ethernet ports
- SFP socket for Easy and Flexible Fiber Expansion
- Redundancy: Gigabit X-Ring (ultra high-speed recovery time<10ms), RSTP/STP (802.1w/1D)
- Management: Web, Telnet, Serial Console, Windows Utility and SNMP
- Control: VLAN/GVRP, QOS, IGMP Snooping, LACP, and Rate Limit
- Security: IP/MAC and port binding, DHCP Server, IP access list, 802.1x, SNMPv3
- Diagnostic: Port Statistic, Port Mirroring, RMON, Trap, SNMP Alert, and Syslog
- Supports 48 V_{DC} power input
- Robust mechanism and special heat spreader design

1.3 Specification

Communications

Standard	IEEE 802.3, 802.3u, 802.3x, 802.3z, 802.1d IEEE 802.1w, 802.1p, 802.1Q, 802.1X, 802.3ad, 802.3af
LAN	10/100/1000Base-TX, Optional 100Base-FX, 1000Base-SX/LX/LHX/XD/ZX/EZX
Transmission Distance	Ethernet: Up to 100m (4-wire Cat.5e, Cat.6 RJ-45 cable suggested for Gigabit port) SFP: Up to 110km (depends on SFP)
Transmission Speed	Ethernet: 10/100Mbps, Auto-Negotiation Gigabit Copper: Up to 1000 Mbps Gigabit Fiber: Up to 1000Mbps

Interface

Connectors	8 x RJ-45 (Ethernet) 2 x RJ-45/SFP (mini-GBIC) combo ports 6-pin removable screw terminal (power & Relay)
LED Indicators	System: PWR, PWR1, PWR2, R.M., P-Fail 10/100TX: Link/Activity, Duplex/Collision Gigabit Copper: Link/Activity, Speed (1000Mbps) SFP: Link/Activity
Console	RS-232 (RJ-45)

Power

Power Consumption	116 W
Power Input	2 x Unregulated 48 V_{DC}
Fault Output	1 Relay Output

Mechanism

Dimensions (WxHxD)	79 x 152 x 105 mm
Enclosure	IP30, metal shell with solid mounting kits
Mounting	DIN-rail, wall

Protection

ESD (Ethernet)	4,000 V_{DC}
Surge (EFT for power)	3,000 V_{DC}
Reverse Polarity	Present

Overload	3.5A@12VDC (Fuse)

Environment

Operating Temperature	-10 ~ 60 ℃ (14 ~ 140 ℉) EKI-7659CPI (Wide temp.): -40~75 ℃ (-40~167 ℉)
Operating Humidity	5 ~ 95% (non-condensing)
Storage Temperature	-40 ~ 85 ℃ (-40~185 ℉)
Storage Humidity	5 ~ 95% (non-condensing)
MTBF	190287 hours

Certifications

Safety	UL, 60950-1, CAN/CSA-C22.2 No.60950
EMC	EU: EN55011, EN61000-6-4 EN55022, Class A, EN61000-3-2/3 EN55024 IEC61000-4-2/3/4/5/6/8 EN61000-6-2
Freefall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6

1.4 Packing List

- 1 x EKI-7659CPI Industrial Managed Gigabit Ethernet Switch
- 1 x eAutomation Industrial Communication CD-ROM with User manual
- 2 x Wall Mounting Bracket and Screws
- 1 x DIN-rail Mounting Bracket and Screws
- 1 x 8-pin RJ-45 to RS-232 serial cable
- 1 x DC Jack Cable φ 2.0/150mm
- 1 x EKI-7659CPI Startup Manual

1.5 Safety Precaution

Attention *IF DC voltage is supplied by an external circuit, please use a protection device on the power supply input.*

CHAPTER 2

Installation

Sections include:

- LED Indicators
- Dimensions
- Mounting
- Network Connection
- Connection to a Fiber Optic Network
- Power Connection

Chapter 2 Installation

In this chapter, you will be given an overview of the EKI-7659CPI hardware installation procedures.

2.1 LED Indicators

There are few LEDs display the power status and network status located on the front panel of EKI-7659CPI, each of them has its own specific meaning shown as below.

Table 2.1: EKI-7659CPI LED Definition

LED	Color	Description	
PWR	Green	On	System power on
		Off	No power input
R.M.	Green	On	The industrial switch is the master of the X-ring group
		Off	The industrial switch is not the master of the X-ring group
PWR1	Green	On	Power input 1 is active
		Off	Power input 1 is inactive
PWR2	Green	On	Power input 2 is active
		Off	Power input 2 is inactive
P-Fail	Red	On	Power input 1 or 2 is inactive or port link down (depends on Fault Relay Alarm configuration)
		Off	Power input 1 and 2 are both active, or no power input
Link/Active (for G9, G10 SFP)	Green	On	SFP port is linking
		Flashing	Data is transmitting or receiving
		Off	Not connected to network
G9, G10 (RJ-45)	Green (Upper LED)	On	The port is operating at speed of 1000M
		Off	The port is disconnected or not operating at speed of 1000M
	Green (Lower LED)	On	Connected to network
		Flashing	Networking is active
		Off	Not connected to network
Link/Active (1~8)	Green	On	Connected to network
		Flashing	Networking is active
		Off	Not connected to network
Duplex/Collision (1~8)	Orange	On	Ethernet port full duplex
		Flashing	Collision of packets occurs
		Off	Ethernet port half duplex or not connected to network

PoE (P1 ~ P8)	Green	On	A powered device is connected utilizing Power over Ethernet on the port
		Off	No device is connected or power forwarding fails

2.2 Dimensions (units: mm)



Figure 2.1: Front View of EKI-7659CPI



Figure 2.2: Side View of EKI-7659CPI



Figure 2.3: Rear View of EKI-7659CPI



Figure 2.4: Top View of EKI-7659CPI

2.3 Mounting

The EKI-7659CPI supports two mounting methods: DIN-rail & Wall.

2.3.1 Wall mounting

EKI-7659CPI can be wall-mounted by using the included mounting kit. Then, hang on the EKI-7659CPI to the nails on the wall.
First, use the screws included in the package to combine the EKI-7659CPI and metal mounting kit. And then you can install the device firmly via the components, please see Figure 2.5 as below.

Figure 2.5: Combine the Metal Mounting Kit (units: mm)

2.3.2 DIN-rail Mounting

You can also mount EKI-7659CPI on a standard DIN-rail by steps below.

The DIN-rail kit is screwed on the industrial switch when out of factory. If the DIN-rail kit is not screwed on the industrial switch, please screw the DIN-rail kit on the switch first.

First, hang the EKI-7659CPI to the DIN-rail with angle of inclination. See Figure 2.6.

Figure 2.6: Installation to DIN-rail Step 1

Then, let the device down straight to slide over the rail smoothly. See Figure 2.7.

Figure 2.7: Installation to DIN-rail Step 2

2.4 Network Connection

The EKI-7659CPI has 8 x RJ-45 ports that support connection to 10 Mbps Ethernet, or 100 Mbps Fast Ethernet, and half or full duplex operation. EKI-7659CPI can be connected to other hubs or switches via a twisted-pair straight-through or crossover cable up to 100m long. The connection can be made from any TX port of the EKI-7659CPI (MDI-X) to another hub or switch either MDI-X or uplink MDI port.

The EKI-7659CPI supports auto-crossover to make networking more easy and flexible. You can connect any RJ-45 (MDI-X) station port on the switch to any device such as a switch, bridge or router.

2.5 Connection to a Fiber Optic Network

EKI-7659CPI has two SFP slots for connecting to the network segment with single or multi-mode fiber. You can choose appropriate mini-GBIC module to plug into the slot. Make sure the module is aligned correctly and then slide the module into the SFP slot until a click is heard. You can use proper multi-mode or single-mode fiber according to the used SFP module. With fiber optic, it transmits speed up to 1000 Mbps and you can prevent noise interference from the system and transmission distance up to 110 km, depending on the mini-GBIC module.

The small form-factor pluggable (SFP) is a compact optical transceiver used in optical communications for both telecommunication and data communications applications.

Note *The SFP/Copper Combo port can be used at one time either. The SFP port has the higher priority than copper port; if you insert the 1000M SFP transceiver into the SFP port which is connected to the remote device, the connection of the accompanying copper port will link down.*
If you insert the 100M SFP transceiver into the SFP port even without a fiber connection to the remote, the connection of the accompanying copper port will link down immediately.

To connect the transceiver and LC cable, please follow the steps shown below:

First, insert the transceiver into the SFP module. Notice that the triangle mark is the bottom of the module.



Figure 2.8: Transceiver to the SFP module



Figure 2.9: Transceiver Inserted

Second, insert the fiber cable of LC connector into the transceiver.



Figure 2.10: LC connector to the transceiver

To remove the LC connector from the transceiver, please follow the steps shown below:

First, press the upper side of the LC connector to release from the transceiver and pull it out.



Figure 2.11: Remove LC connector

Second, push down the metal loop and pull the transceiver out by the plastic handle.



Figure 2.12: Pull out from the transceiver

2.6 Power Connection

The EKI-7659CPI supports dual +12 ~ 48 V_{DC} power inputs and power-fail relay output.



Figure 2.8: Pin Assignment of the Power Connector

You can connect an alarm indicator, buzzer or other signaling equipment through the relay output. The relay opens if power input 1, 2 fails or port link down/break (″Open″ means if you connect relay output with an LED, the light would be off).

CHAPTER 3

Configuration

Sections include:

- RS-232 Console
- Web Browser
- Mounting
- Self Diagnosis

Chapter 3 Configuration

The EKI-7659CPI can be configured in two ways: via RS-232 Console or a web browser.

3.1 RS-232 Console

EKI-7659CPI's RS-232 console is designed for rapidly configuring which provides the console management – CLI command.

Attach the supplied cable, which one end is RJ-45 and the other end is female DB9, to connect EKI-7659CPI and your host PC or terminal. The connected PC or terminal must support the terminal emulation program.



From the Windows desktop, click:
Start/Programs/Accessories/Communications/HyperTerminal
to open Hyper Terminal program.



Figure 3.1: Open Hyper Terminal

Select the appropriate COM port, and set the parameter as Fig.3.2 (**9600** for **Baud Rate**, **8** for **Data Bits**, **None** for **Parity**, **1** for **Stop Bits**, and **None** for **Flow Control**).



Figure 3.2: COM Port Properties Setting

Press **Enter** for login screen (If you can not find the login screen, press **Enter** one more time). The default user name and password are both "**admin**". Key-in the user name and password to enter the command line interface.



Figure 3.3: Login Screen: RS-232 Configuration

After you have logged in to the system, you will see a command prompt. To enter CLI management interface, type in "**enable**" command.



Figure 3.4: Command Line Interface

The following table lists the CLI commands and description.

3.1.1 Commands Level

Table 3.1: Command Level

Modes	Access Method	Prompt	Exit Method	About This Model
User EXEC	Begin a session with your switch.	switch>	Enter **logout** or **quit**.	The user commands available at the user level are a subset of those available at the privileged level. Use this mode to • Perform basic tests. • Display system information.
Privileged EXEC	Enter the **enable** command while in user EXEC mode.	switch#	Enter **disable** to exit.	The privileged command is the advance mode Use this mode to • Display advanced function status • save configuration
Global configuration	Enter the **configure** command while in privileged EXEC mode.	switch(config)#	To exit to privileged EXEC mode, enter **exit** or **end**	Use this mode to configure the parameters that are going to be applied to your switch
VLAN database	Enter the **vlan database** command while in privileged EXEC mode.	switch(vlan)#	To exit to user EXEC mode, enter **exit**.	Use this mode to configure VLAN-specific parameters.
Interface configuration	Enter the **interface** command (with a specific interface) while in global configuration mode	switch(config-if)#	To exit to global configuration mode, enter **exit**. To exist to privileged EXEC mode, enter **exit** or **end.**	Use this mode to configure the parameters for the switch and Ethernet ports.

3.1.2 Commands Set List

Table 3.2: Commands Set List

Command	Code Word
User EXEC	E
Privileged EXEC	P
Global configuration	G
VLAN database	V
Interface configuration	I

3.1.3 System Commands Set

Table 3.3: System Commands Set

Commands	Level	Description	Example
show config	E	Show switch configuration	switch>**show config**
show terminal	P	Show console information	switch#**show terminal**
write memory	P	Save user configuration into permanent memory (flash rom)	switch#**write memory**
system name [System Name]	G	Configure system name	switch(config)#**system name xxx**
system location [System Location]	G	Set switch system location string	switch(config)#**system location xxx**
system description [System Description]	G	Set switch system description string	switch(config)#**system description xxx**
system contact [System Contact]	G	Set switch system contact window string	switch(config)#**system contact xxx**
show system-info	E	Show system information	switch>**show system-info**
ip address [Ip-address] [Subnet-mask] [Gateway]	G	Configure the IP address of switch	switch(config)#**ip address 192.168.1.1 255.255.255.0 192.168.1.254**
ip dhcp	G	Enable DHCP client function of switch	switch(config)#**ip dhcp**
show ip	P	Show IP information of switch	switch#**show ip**
no ip dhcp	G	Disable DHCP client function of switch	switch(config)#**no ip dhcp**
reload	G	Halt and perform a cold restart	switch(config)#**reload**
default	G	Restore to default	switch(config)#**default**
admin username [Username]	G	Changes a login username. (maximum 10 words)	switch(config)#**admin username xxxxxx**
admin password [Password]	G	Specifies a password (maximum 10 words)	switch(config)#**admin password xxxxxx**
show admin	P	Show administrator information	switch#**show admin**
dhcpserver enable	G	Enable DHCP Server	switch(config)#**dhcpserver enable**
Dhcpserver disable	G	Disable DHCP Server	switch(config)#**no dhcpserver**
dhcpserver lowip [Low IP]	G	Configure low IP address for IP pool	switch(config)#**dhcpserver lowip 192.168.1.100**
dhcpserver highip [High IP]	G	Configure high IP address for IP pool	switch(config)#**dhcpserver highip 192.168.1.200**

dhcpserver subnetmask [Subnet mask]	G	Configure subnet mask for DHCP clients	switch(config)#**dhcpserver subnetmask 255.255.255.0**
dhcpserver gateway [Gateway]	G	Configure gateway for DHCP clients	switch(config)#**dhcpserver gateway 192.168.1.254**
dhcpserver dnsip [DNS IP]	G	Configure DNS IP for DHCP clients	switch(config)#**dhcpserver dnsip 192.168.1.1**
dhcpserver leasetime [Hours]	G	Configure lease time (in hour)	switch(config)#**dhcpserver leasetime 1**
dhcpserver ipbinding [IP address]	I	Set static IP for DHCP clients by port	switch(config)#**interface fastEthernet 2** switch(config)#**dhcpserver ipbinding 192.168.1.1**
show dhcpserver configuration	P	Show configuration of DHCP server	switch#**show dhcpserver configuration**
show dhcpserver clients	P	Show client entries of DHCP server	switch#**show dhcpserver clients**
show dhcpserver ip-binding	P	Show IP-Binding information of DHCP server	switch#**show dhcpserver ip-binding**
no dhcpserver	G	Disable DHCP server function	switch(config)#**no dhcpserver**
security enable	G	Enable IP security function	switch(config)#**security enable**
security http	G	Enable IP security of HTTP server	switch(config)#**security http**
security telnet	G	Enable IP security of telnet server	switch(config)#**security telnet**
security ip [Index(1..10)] [IP Address]	G	Set the IP security list	switch(config)#**security ip 1 192.168.1.55**
show security	P	Show the information of IP security	switch#**show security**
no security	G	Disable IP security function	switch(config)#**no security**
no security http	G	Disable IP security of HTTP server	switch(config)#**no security http**
no security telnet	G	Disable IP security of telnet server	switch(config)#**no security telnet**

3.1.4 Port Commands Set

Table 3.4: Port Commands Set

Commands	Level	Description	Example
interface fastEthernet [Portid]	G	Choose the port for modification.	switch(config)#**interface fastEthernet 2**
duplex [full | half]	I	Use the duplex configuration command to specify the duplex mode of operation for Fast Ethernet.	switch(config)#**interface fastEthernet 2** switch(config-if)**#duplex full**
speed [10|100|1000|auto]	I	Use the speed configuration command to specify the speed mode of operation for Fast Ethernet., the speed can't be set to 1000 if the port isn't a giga port..	switch(config)#**interface fastEthernet 2** switch(config-if)**#speed 100**
no flowcontrol	I	Disable flow control of interface	switch(config-if)#**no flowcontrol**
security enable	I	Enable security of interface	switch(config)#**interface fastEthernet 2** switch(config-if)**#security enable**
no security	I	Disable security of interface	switch(config)#**interface fastEthernet 2** switch(config-if)#**no security**

bandwidth type all	I	Set interface ingress limit frame type to “accept all frame”	switch(config)#**interface fastEthernet 2** switch(config-if)#**bandwidth type all**
bandwidth type broadcast-multicast-flooded-unicast	I	Set interface ingress limit frame type to “accept broadcast, multicast, and flooded unicast frame”	switch(config)#**interface fastEthernet 2** switch(config-if)#**bandwidth type broadcast-multicast-flooded-unicast**
bandwidth type broadcast-multicast	I	Set interface ingress limit frame type to “accept broadcast and multicast frame”	switch(config)#**interface fastEthernet 2** switch(config-if)#**bandwidth type broadcast-multicast**
bandwidth type broadcast-only	I	Set interface ingress limit frame type to “only accept broadcast frame”	switch(config)#**interface fastEthernet 2** switch(config-if)#**bandwidth type broadcast-only**
bandwidth in [Value]	I	Set interface input bandwidth. Rate Range is from 100 kbps to 102400 kbps or to 256000 kbps for giga ports, and zero means no limit.	switch(config)#**interface fastEthernet 2** switch(config-if)#**bandwidth in 100**
bandwidth out [Value]		Set interface output bandwidth. Rate Range is from 100 kbps to 102400 kbps or to 256000 kbps for giga ports, and zero means no limit.	switch(config)#**interface fastEthernet 2** switch(config-if)#**bandwidth out 100**
show bandwidth	I	Show interfaces bandwidth control	switch(config)#**interface fastEthernet 2** switch(config-if)#**show bandwidth**
state [Enable | Disable]	I	Use the state interface configuration command to specify the state mode of operation for Ethernet ports. Use the disable form of this command to disable the port.	switch(config)#**interface fastEthernet 2** switch(config-if)#**state Disable**
show interface configuration	I	show interface configuration status	switch(config)#**interface fastEthernet 2** switch(config-if)#**show interface configuration**
show interface status	I	show interface actual status	switch(config)#**interface fastEthernet 2** switch(config-if)#**show interface status**
show interface accounting	I	show interface statistic counter	switch(config)#**interface fastEthernet 2** switch(config-if)#**show interface accounting**
no accounting	I	Clear interface accounting information	switch(config)#**interface fastEthernet 2** switch(config-if)#**no accounting**

3.1.5 Trunk Commands Set

Table 3.5: Trunk Commands Set

Commands	Level	Description	Example
aggregator priority [1~65535]	G	Set port group system priority	switch(config)#**aggregator priority 22**
aggregator activityport [Group ID] [Port Numbers]	G	Set activity port	switch(config)#**aggregator activityport 2**
aggregator group [GroupID] [Port-list] **lacp** **workp** [Workport]	G	Assign a trunk group with LACP active. [GroupID] :1~3 [Port-list]:Member port list, This parameter could be a port range(ex.1-4) or a port list separate by a comma(ex.2, 3, 6) [Workport]: The amount of work ports, this value could not be less than zero or be large than the amount of member ports.	switch(config)#**aggregator group 1 1-4 lacp workp 2** or switch(config)#**aggregator group 2 1,4,3 lacp workp 3**

aggregator group [GroupID] [Port-list] **nolacp**	G	Assign a static trunk group. [GroupID] :1~3 [Port-list]:Member port list, This parameter could be a port range(ex.1-4) or a port list separate by a comma(ex.2, 3, 6)	switch(config)#**aggregator group 1 2-4 nolacp** or switch(config)#**aggregator group 1 3,1,2 nolacp**
show aggregator	P	Show the information of trunk group	switch#**show aggregator 1** or switch#**show aggregator 2** or switch#**show aggregator 3**
no aggregator lacp [GroupID]	G	Disable the LACP function of trunk group	switch(config)#**no aggreator lacp 1**
no aggregator group [GroupID]	G	Remove a trunk group	switch(config)#**no aggreator group 2**

3.1.6 VLAN Commands Set

Table 3.6: VLAN Commands Set

Commands	Level	Description	Example
vlan database	P	Enter VLAN configure mode	switch#**vlan database**
Vlanmode [portbase| 802.1q | gvrp]	V	To set switch VLAN mode.	switch(vlan)#**vlanmode portbase** or switch(vlan)#**vlanmode 802.1q** or switch(vlan)#**vlanmode gvrp**
no vlan	V	No VLAN	Switch(vlan)#**no vlan**
Ported based VLAN configuration			
vlan port-based grpname [Group Name] **grpid** [GroupID] **port** [PortNumbers]	V	Add new port based VALN	switch(vlan)#**vlan port-based grpname test grpid 2 port 2-4** or switch(vlan)#**vlan port-based grpname test grpid 2 port 2,3,4**
show vlan [GroupID] or **show vlan**	V	Show VLAN information	switch(vlan)#**show vlan 23**
no vlan group [GroupID]	V	Delete port base group ID	switch(vlan)#**no vlan group 2**
IEEE 802.1Q VLAN			
vlan 8021q name [GroupName] **vid** [VID]	V	Change the name of VLAN group, if the group didn't exist, this command can't be applied.	switch(vlan)#**vlan 8021q name test vid 22**
vlan 8021q port [PortNumber] **access-link untag** [UntaggedVID]	V	Assign a access link for VLAN by port, if the port belong to a trunk group, this command can't be applied.	switch(vlan)#**vlan 8021q port 3 access-link untag 33**
vlan 8021q port [PortNumber] **trunk-link tag** [TaggedVID List]	V	Assign a trunk link for VLAN by port, if the port belong to a trunk group, this command can't be applied.	switch(vlan)#**vlan 8021q port 3 trunk-link tag 2,3,6,99** or switch(vlan)#**vlan 8021q port 3 trunk-link tag 3-20**
vlan 8021q port [PortNumber] **hybrid-link untag** [UntaggedVID] **tag** [TaggedVID List]	V	Assign a hybrid link for VLAN by port, if the port belong to a trunk group, this command can't be applied.	switch(vlan)#**vlan 8021q port 3 hybrid-link untag 4 tag 3,6,8** or switch(vlan)#**vlan 8021q port 3 hybrid-link untag 5 tag 6-8**

vlan 8021q trunk [PortNumber] **access-link untag** [UntaggedVID]	V	Assign a access link for VLAN by trunk group	switch(vlan)#**vlan 8021q trunk 3 access-link untag 33**
vlan 8021q trunk [PortNumber] **trunk-link tag** [TaggedVID List]	V	Assign a trunk link for VLAN by trunk group	switch(vlan)#**vlan 8021q trunk 3 trunk-link tag 2,3,6,99** or switch(vlan)#**vlan 8021q trunk 3 trunk-link tag 3-20**
vlan 8021q trunk [PortNumber] **hybrid-link untag** [UntaggedVID] **tag** [TaggedVID List]	V	Assign a hybrid link for VLAN by trunk group	switch(vlan)#**vlan 8021q trunk 3 hybrid-link untag 4 tag 3,6,8** or switch(vlan)#**vlan 8021q trunk 3 hybrid-link untag 5 tag 6-8**
show vlan [GroupID] or **show vlan**	V	Show VLAN information	switch(vlan)#**show vlan 23**
no vlan group [GroupID]	V	Delete port base group ID	switch(vlan)#**no vlan group 2**

3.1.7 Spanning Tree Commands Set

Table 3.7: Spanning Tree Commands Set

Commands	Level	Description	Example
spanning-tree enable	G	Enable spanning tree	switch(config)#**spanning-tree enable**
spanning-tree priority [0~61440]	G	Configure spanning tree priority parameter	switch(config)#**spanning-tree priority 32767**
spanning-tree max-age [seconds]	G	Use the spanning-tree max-age global configuration command to change the interval between messages the spanning tree receives from the root switch. If a switch does not receive a bridge protocol data unit (BPDU) message from the root switch within this interval, it recomputed the Spanning Tree Protocol (STP) topology.	switch(config)#**spanning-tree max-age 15**
spanning-tree hello-time [seconds]	G	Use the spanning-tree hello-time global configuration command to specify the interval between hello bridge protocol data units (BPDUs).	switch(config)#**spanning-tree hello-time 3**
spanning-tree forward-time [seconds]	G	Use the spanning-tree forward-time global configuration command to set the forwarding-time for the specified spanning-tree instances. The forwarding time determines how long each of the listening and learning states last before the port begins forwarding.	switch(config)#**spanning-tree forward-time 20**
stp-path-cost [1~200000000]	I	Use the spanning-tree cost interface configuration command to set the path cost for Spanning Tree Protocol (STP) calculations. In the event of a loop, spanning tree considers the path cost when selecting an interface to place into the forwarding state.	switch(config)#**interface fastEthernet 2** switch(config-if)#**stp-path-cost 20**
stp-path-priority [Port Priority]	I	Use the spanning-tree port-priority interface configuration command to configure a port priority that is used when two switches tie for	switch(config)#**interface fastEthernet 2** switch(config-if)#**stp-path-priority 128**

		position as the root switch.	
stp-admin-p2p [Auto|True|False]	I	Admin P2P of STP priority on this interface.	switch(config)#**interface fastEthernet 2** switch(config-if)#**stp-admin-p2p Auto**
stp-admin-edge [True|False]	I	Admin Edge of STP priority on this interface.	switch(config)#**interface fastEthernet 2** switch(config-if)#**stp-admin-edge True**
stp-admin-non-stp [True|False]	I	Admin NonSTP of STP priority on this interface.	switch(config)#**interface fastEthernet 2** switch(config-if)#**stp-admin-non-stp False**
show spanning-tree	E	Displays a summary of the spanning-tree states.	switch>**show spanning-tree**
no spanning-tree	G	Disable spanning-tree.	switch(config)#**no spanning-tree**

3.1.8 QOS Commands Set

Table 3.8: QOS Commands Set

Commands	Level	Description	Example
qos policy [weighted-fair|strict]	G	Select QOS policy scheduling	switch(config)#**qos policy weighted-fair**
qos prioritytype [port-based|cos-only|tos-only|cos-first|tos-first]	G	Setting of QOS priority type	switch(config)#**qos prioritytype**
qos priority portbased [Port] [lowest|low|middle|high]	G	Configure Port-based Priority	switch(config)#**qos priority portbased 1 low**
qos priority cos [Priority][lowest|low|middle|high]	G	Configure COS Priority	switch(config)#**qos priority cos 0 middle**
qos priority tos [Priority][lowest|low|middle|high]	G	Configure TOS Priority	switch(config)#**qos priority tos 3 high**
show qos	P	Displays the information of QoS configuration	Switch#**show qos**
no qos	G	Disable QoS function	switch(config)#**no qos**

3.1.9 IGMP Commands Set

Table 3.9: QOS Commands Set

Commands	Level	Description	Example
igmp enable	G	Enable IGMP snooping function	switch(config)#**igmp enable**
Igmp-query auto	G	Set IGMP query to auto mode	switch(config)#**Igmp-query auto**
Igmp-query force	G	Set IGMP query to force mode	switch(config)#**Igmp-query force**
show igmp configuration	P	Displays the details of an IGMP configuration.	switch#**show igmp configuration**
show igmp multi	P	Displays the details of an IGMP snooping entries.	switch#**show igmp multi**
no igmp	G	Disable IGMP snooping function	switch(config)#**no igmp**
no igmp-query	G	Disable IGMP query	switch#**no igmp-query**

3.1.10 Mac/Filter Table Commands Set

Table 3.10: Mac/Filter Table Commands Set

Commands	Level	Description	Example
mac-address-table static hwaddr [MAC]	I	Configure MAC address table of interface (static).	switch(config)#**interface fastEthernet 2** switch(config-if)#**mac-address-table static hwaddr 000012345678**
mac-address-table filter hwaddr [MAC]	G	Configure MAC address table(filter)	switch(config)#**mac-address-table filter hwaddr 000012348678**
show mac-address-table	P	Show all MAC address table	switch#**show mac-address-table**
show mac-address-table static	P	Show static MAC address table	switch#**show mac-address-table static**
show mac-address-table filter	P	Show filter MAC address table.	switch#**show mac-address-table filter**
no mac-address-table static hwaddr [MAC]	I	Remove an entry of MAC address table of interface (static)	switch(config)#**interface fastEthernet 2** switch(config-if)#**no mac-address-table static hwaddr 000012345678**
no mac-address-table filter hwaddr [MAC]	G	Remove an entry of MAC address table (filter)	switch(config)#**no mac-address-table filter hwaddr 000012348678**
no mac-address-table	G	Remove dynamic entry of MAC address table	switch(config)#**no mac-address-table**

3.1.11 SNMP Commands Set

Table 3.11: SNMP Commands Set

Commands	Level	Description	Example
snmp system-name [System Name]	G	Set SNMP agent system name	switch(config)#**snmp system-name l2switch**
snmp system-location [System Location]	G	Set SNMP agent system location	switch(config)#**snmp system-location lab**
snmp system-contact [System Contact]	G	Set SNMP agent system contact	switch(config)#**snmp system-contact where**
snmp agent-mode [v1v2c|v3|v1v2cv3]	G	Select the agent mode of SNMP	switch(config)#**snmp agent-mode v1v2cv3**
snmp community-strings [Community] **right** [RO/RW]	G	Add SNMP community string.	switch(config)#**snmp community-strings public right rw**
snmp-server host [IP address] **community** [Community-string] **trap-version** [v1|v2c]	G	Configure SNMP server host information and community string	switch(config)#**snmp-server host 192.168.1.50 community public trap-version v1 (remove)** Switch(config)# **no snmp-server host 192.168.1.50**
snmpv3 context-name [Context Name]	G	Configure the context name	switch(config)#**snmpv3 context-name Test**
snmpv3 user [User Name] **group** [Group Name] **password** [Authentication Password] [Privacy Password]	G	Configure the userprofile for SNMPV3 agent. Privacy password could be empty.	switch(config)#**snmpv3 user test01 group G1 password AuthPW PrivPW**
snmpv3 access context-name [Context Name] **group** [Group Name] **security-level** [NoAuthNoPriv|AuthNoPriv|AuthPriv] **match-rule** [Exact|Prifix] **views** [Read View Name] [Write View Name] [Notify View Name]	G	Configure the access table of SNMPV3 agent	switch(config)#**snmpv3 access context-name Test group G1 security-level AuthPriv match-rule Exact views V1 V1 V1**
snmpv3 mibview view [View Name] **type** [Excluded|Included]	G	Configure the mibview table of SNMPV3 agent	switch(config)#**snmpv3 mibview view V1 type Excluded sub-oid 1.3.6.1**

sub-oid [OID]			
show snmp	**P**	Show SNMP configuration	switch#**show snmp**
no snmp community-strings [Community]	**G**	Remove the specified community.	switch(config)#**no snmp community-strings public**
no snmp-server host [Host-address]	**G**	Remove the SNMP server host.	switch(config)#**no snmp-server 192.168.1.50**
no snmpv3 user [User Name]	**G**	Remove specified user of SNMPv3 agent.	switch(config)#**no snmpv3 user Test**
no snmpv3 access context-name [Context Name] **group** [Group Name] **security-level** [NoAuthNoPriv|AuthNoPriv|AuthPriv] **match-rule** [Exact|Prifix] **views** [Read View Name] [Write View Name] [Notify View Name]	**G**	Remove specified access table of SNMPv3 agent.	switch(config)#**no snmpv3 access context-name Test group G1 security-level AuthPr iv match-rule Exact views V1 V1 V1**
no snmpv3 mibview view [View Name] **type** [Excluded|Included] **sub-oid** [OID]	**G**	Remove specified mibview table of SNMPV3 agent.	switch(config)#**no snmpv3 mibview view V1 type Excluded sub-oid 1.3.6.1**

3.1.12 Port Mirroring Commands Set

Table 3.12: Port Mirroring Commands Set

Commands	Level	Description	Example
monitor rx	**G**	Set RX destination port of monitor function	switch(config)#**monitor rx**
monitor tx	**G**	Set TX destination port of monitor function	switch(config)#**monitor tx**
show monitor	**P**	Show port monitor information	switch#**show monitor**
monitor [RX|TX|Both]	**I**	Configure source port of monitor function	switch(config)#**interface fastEthernet 2** switch(config-if)#**monitor RX**
show monitor	**I**	Show port monitor information	switch(config)#**interface fastEthernet 2** switch(config-if)#**show monitor**
no monitor	**I**	Disable source port of monitor function	switch(config)#**interface fastEthernet 2** switch(config-if)#**no monitor**

3.1.13 802.1x Commands Set

Table 3.13: 802.1x Commands Set

Commands	Level	Description	Example
8021x enable	**G**	Use the 802.1x global configuration command to enable 802.1x protocols.	switch(config)# **8021x enable**
8021x system radiousip **[IP address]**	**G**	Use the 802.1x system radious IP global configuration command to change the radious server IP.	switch(config)# **8021x system radiousip 192.168.1.1**
8021x system serverport **[port ID]**	**G**	Use the 802.1x system server port global configuration command to	switch(config)# **8021x system serverport 1815**

		change the radious server port	
8021x system accountport [port ID]	G	Use the 802.1x system account port global configuration command to change the accounting port	switch(config)# **8021x system accountport 1816**
8021x system sharekey [ID]	G	Use the 802.1x system share key global configuration command to change the shared key value.	switch(config)# **8021x system sharekey 123456**
8021x system nasid [words]	G	Use the 802.1x system nasid global configuration command to change the NAS ID	switch(config)# **8021x system nasid test1**
8021x misc quietperiod [sec.]	G	Use the 802.1x misc quiet period global configuration command to specify the quiet period value of the switch.	switch(config)# **8021x misc quietperiod 10**
8021x misc txperiod [sec.]	G	Use the 802.1x misc TX period global configuration command to set the TX period.	switch(config)# **8021x misc txperiod 5**
8021x misc supportimeout [sec.]	G	Use the 802.1x misc supp timeout global configuration command to set the supplicant timeout.	switch(config)# **8021x misc supportimeout 20**
8021x misc servertimeout [sec.]	G	Use the 802.1x misc server timeout global configuration command to set the server timeout.	switch(config)#**8021x misc servertimeout 20**
8021x misc maxrequest [number]	G	Use the 802.1x misc max request global configuration command to set the MAX requests.	switch(config)# **8021x misc maxrequest 3**
8021x misc reauthperiod [sec.]	G	Use the 802.1x misc reauth period global configuration command to set the reauth period.	switch(config)# **8021x misc reauthperiod 3000**
8021x portstate [disable | reject | accept | authorize]	I	Use the 802.1x port state interface configuration command to set the state of the selected port.	switch(config)#**interface fastethernet 3** switch(config-if)#**8021x portstate accept**
show 8021x	E	Displays a summary of the 802.1x properties and also the port sates.	switch>**show 8021x**
no 8021x	G	Disable 802.1x function	switch(config)#**no 8021x**

3.1.14 TFTP Commands Set

Table 3.14: TFTP Commands Set

Commands	Level	Description	Defaults Example
backup flash:backup_cfg	G	Save configuration to TFTP and need to specify the IP of TFTP server and the file name of image.	switch(config)#**backup flash:backup_cfg**
restore flash:restore_cfg	G	Get configuration from TFTP server and need to specify the IP of TFTP server and the file name of image.	switch(config)#**restore flash:restore_cfg**
upgrade flash:upgrade_fw	G	Upgrade firmware by TFTP and need to specify the IP of TFTP server and the file name of image.	switch(config)#**upgrade lash:upgrade_fw**

3.1.15 SystemLog, SMTP and Event

Table 3.15: SysLog,SMTP,Event Commands Set

Commands	Level	Description	Example
systemlog ip [IP address]	G	Set System log server IP address.	switch(config)# **systemlog ip 192.168.1.100**

systemlog mode [client|server|both]	G	Specified the log mode	switch(config)# **systemlog mode both**
show systemlog	E	Displays system log.	Switch>**show systemlog**
show systemlog	P	Show system log client & server information	switch#**show systemlog**
no systemlog	G	Disable systemlog functon	switch(config)#**no systemlog**
smtp enable	G	Enable SMTP function	switch(config)#**smtp enable**
smtp serverip [IP address]	G	Configure SMTP server IP	switch(config)#**smtp serverip 192.168.1.5**
smtp authentication	G	Enable SMTP authentication	switch(config)#**smtp authentication**
smtp account [account]	G	Configure authentication account	switch(config)#**smtp account User**
smtp password [password]	G	Configure authentication password	switch(config)#**smtp password**
smtp rcptemail [Index] [Email address]	G	Configure Rcpt e-mail Address	switch(config)#**smtp rcptemail 1 Alert@test.com**
show smtp	P	Show the information of SMTP	switch#**show smtp**
no smtp	G	Disable SMTP function	switch(config)#**no smtp**
event device-cold-start [Systemlog|SMTP|Both]	G	Set cold start event type	switch(config)#**event device-cold-start both**
event authentication-failure [Systemlog|SMTP|Both]	G	Set Authentication failure event type	switch(config)#**event authentication-failure both**
event X-ring-topology-change [Systemlog|SMTP|Both]	G	Set X - ring topology changed event type	switch(config)#**event X-ring-topology-change both**
event systemlog [Link-UP|Link-Down|Both]	I	Set port event for system log	switch(config)#**interface fastethernet 3** switch(config-if)#**event systemlog both**
event smtp [Link-UP|Link-Down|Both]	I	Set port event for SMTP	switch(config)#**interface fastethernet 3** switch(config-if)#**event smtp both**
show event	P	Show event selection	switch#**show event**
no event device-cold-start	G	Disable cold start event type	switch(config)#**no event device-cold-start**
no event authentication-failure	G	Disable Authentication failure event type	switch(config)#**no event authentication-failure**
no event X-ring-topology-change	G	Disable X - ring topology changed event type	switch(config)#**no event X-ring-topology-change**
no event systemlog	I	Disable port event for system log	switch(config)#**interface fastethernet 3** switch(config-if)#**no event systemlog**
no event smpt	I	Disable port event for SMTP	switch(config)#**interface fastethernet 3** switch(config-if)#**no event smtp**
show systemlog	P	Show system log client & server information	switch#**show systemlog**

3.1.16 SNTP Commands Set

Table 3.16: SNTP Commands Set

Commands	Level	Description	Example
sntp enable	G	Enable SNTP function	switch(config)#**sntp enable**
sntp daylight	G	Enable daylight saving time, if SNTP function is inactive, this command can't be applied.	switch(config)#**sntp daylight**
sntp daylight-period [Start time] [End time]	G	Set period of daylight saving time, if SNTP function is inactive, this command can't be applied. Parameter format: [yyyymmdd-hh:mm]	switch(config)# **sntp daylight-period 20060101-01:01 20060202-01-01**
sntp daylight-offset [Minute]	G	Set offset of daylight saving time, if SNTP function is inactive, this command can't be applied.	switch(config)#**sntp daylight-offset 3**
sntp ip [IP]	G	Set SNTP server IP, if SNTP function is inactive, this command can't be applied.	switch(config)#**sntp ip 192.169.1.1**
sntp timezone [Timezone]	G	Set timezone index, use "show sntp timzezone" command to get more information of index number	switch(config)#**sntp timezone 22**
show sntp	P	Show SNTP information	switch#**show sntp**

show sntp timezone	**P**	Show index number of time zone list	switch#**show sntp timezone**
no sntp	**G**	Disable SNTP function	switch(config)#**no sntp**
no sntp daylight	**G**	Disable daylight saving time	switch(config)#**no sntp daylight**

3.1.17 X-ring Commands Set

Table 3.17: X-ring Commands Set

Commands	Level	Description	Example
Xring enable	**G**	Enable X-ring	switch(config)#**Xring enable**
Xring master	**G**	Enable ring master	switch(config)#**Xring master**
Xring couplering	**G**	Enable couple ring	switch(config)#**Xring couplering**
Xring dualhoming	**G**	Enable dual homing	switch(config)#**Xring dualhoming**
Xring ringport [1st Ring Port] [2nd Ring Port]	**G**	Configure 1st/2nd Ring Port	switch(config)#**Xring ringport 7 8**
Xring couplingport [Coupling Port]	**G**	Configure Coupling Port	switch(config)#**Xring couplingport 1**
Xring controlport [Control Port]	**G**	Configure Control Port	switch(config)#**Xring controlport 2**
Xring homingport [Dual Homing Port]	**G**	Configure Dual Homing Port	switch(config)#**Xring homingport 3**
show Xring	**P**	Show the information of X - Ring	switch#**show Xring**
no Xring	**G**	Disable X-ring	switch(config)#**no Xring**
no Xring master	**G**	Disable ring master	switch(config)# **no Xring master**
no Xring couplering	**G**	Disable couple ring	switch(config)# **no Xring couplering**
no Xring dualhoming	**G**	Disable dual homing	switch(config)# **no Xring dualhoming**

3.1.18 PoE Commands Set

Table 3.18: PoE Commands Set

Commands	Level	Description	Example
poe	**P**	Enter POE configure mode	switch#**poe**
system knockoff-disabled [Enable|Disable]	**P**	Set PoE system Port Knockoff Disabled	switch(poe)# **system knockoff-disabled disable**
system ac-disconnect [Enable|Disable]	**P**	Set PoE system AC Disconnect	switch(poe)# **system ac-disconnect disable**
system capacitive-detect [Enable|Disable]	**P**	Set PoE system Capacitive Detection	switch(poe)# **system capacitive-detect enable**
system power-limit [Value]	**P**	Set Poe system Power Limit	switch(poe)# **system power-limit 90**
port [PortNumbers] **state** [Enable|Disable]	**P**	Set PoE port State	switch(poe)# **port 1 state disable**
port [PortNumbers] **plfc** [Enable|Disable]	**P**	Set PoE port Power Limit from Classification	switch(poe)# **port 1 plfc enable**
port [PortNumbers] **legacy** [Enable|Disable]	**P**	Set PoE port Legacy	switch(poe)# **port 1 legacy enable**
port [PortNumbers] **priority** [Low|High|Critical]	**P**	Set PoE port Priority	switch(poe)# **port 1 priority high**
port [PortNumbers] **powerlimit** [Value]	**P**	Set PoE port Power Limit Value	switch(poe)# **port 1 powerlimit 15300**
show poe	**P**	Show setting of PoE function	switch#**show poe**

3.2 Web Browser

EKI-7659CPI provides a convenient configuring way via web browser. You can follow the steps below to access EKI-7659CPI.
EKI-7659CPI's default IP is 192.168.1.1. Make sure your host PC and EKI-7659 are on the same logical sub-network.

Warning *Your host PC should be in the same VLAN setting with EKI-7659CPI, or the management will not be configured.*

Connect EKI-7659CPI to the Ethernet then your host PC could be configured via Ethernet. Or you can directly connect EKI-7659CPI to your host PC with a straight-through or cross over Ethernet cable.

Before to use web management, install the industrial switch on the network and make sure that any one of PCs on the network can connect with the industrial switch through the web browser. The industrial switch default value of IP, subnet mask, username and password are as below:

- IP Address: 192.168.1.1
- Subnet Mask: 255.255.255.0
- Default Gateway: 192.168.1.254
- User Name: admin
- Password: admin

Open Internet Explorer and type EKI-7659CPI's IP in the Address field then press Enter to open the web login page.

Figure 3.5: Type the address in the URL

Figure 3.6: Web Login Window

The default user name and password are both **admin**, fill in the user name and password then press **OK** to enter the configuration. You can change the password in the system setting.

In the main page, you can find the tree menu structure of the EKI-7659CPI in the left side. Click the "+" symbol to unroll the hiding hyperlink, and click the hyperlink to open the function page you want to configure.



Figure 3.7: Main page

3.2.1 System

System Information

Here you can view the system information and assign the system name and location to make this switch more easily to be identified on your network.

- **System Name**: Assign the name of the switch. The maximum length is 64 bytes.
- **System Description**: Displays the description of switch. Read only cannot be modified.
- **System Location**: Assign the switch physical location. The maximum length is 64 bytes.
- **System Contact**: Enter the name of contact person or organization.
- **Firmware Version**: Displays the switch's firmware version.
- **Kernel Version**: Displays the kernel software version.
- **MAC Address**: Displays the unique hardware address assigned by manufacturer (default).

Warning *Don't set "0" for the first segment of the subnet mask and default gateway (000.xxx.xxx.xxx).*
Refresh the web screen if the web could not be displayed while you change the setting.



Figure 3.8: System Information

IP Configuration

User can configure the IP Settings and DHCP client function here.

- **DHCP Client**: To enable or disable the DHCP client function. When DHCP client function is enabled, the industrial switch will be assigned the IP address from the network DHCP server. The default IP address will be replaced by the DHCP server assigned IP address. After user click “Apply” button, a popup dialog show up. It is to inform the user that when the DHCP client is enabling, the current IP will lose and user should find the new IP on the DHCP server.
- **IP Address**: Assign the IP address that the network is using. If DHCP client function is enabling, and then user doesn’t need to assign the IP address. And, the network DHCP server will assign the IP address for the industrial switch and displays in this column. The default IP is 192.168.1.1.
- **Subnet Mask**: Assign the subnet mask of the IP address. If DHCP client function is enabling, and then user does not need to assign the subnet mask.
- **Gateway**: Assign the network gateway for the industrial switch. The default gateway is 192.168.1.254.
- **DNS1**: The abbreviation of Domain Name Server—an Internet service that translate domain name into IP addresses. Domain name are alphabetic which are easy to be remembered. Because the Internet is based on IP address; every time you use a domain name, therefore, a DNS service must translate the name into the corresponding IP address. For example, the domain name **www.net.com** might translate to 192.168.1.1
- **DNS2**: The backup for DNS1. When DNS1 cannot function, DNS2 will then replace DNS1 immediately.
- And then, click 



Figure 3.9: IP Configuration

DHCP Server – System configuration

DHCP is the abbreviation of Dynamic Host Configuration Protocol that is a protocol for assigning dynamic IP addresses to devices on a network. With dynamic addressing, a device can have a different IP address every time it connects to the network. In some systems, the device's IP address can even change while it is still connected. DHCP also supports a mix of static and dynamic IP addresses. Dynamic addressing simplifies network administration because the software keeps track of IP addresses rather than requiring an administrator to manage the task. This means that a new computer can be added to a network without the hassle of manually assigning it a unique IP address.
The system provides the DHCP server function. Enable the DHCP server function, the switch system will be a DHCP server.

- **DHCP Server:** Enable or Disable the DHCP Server function. Enable – the switch will be the DHCP server on your local network.
- **Low IP Address:** the dynamic IP assign range. Low IP address is the beginning of the dynamic IP assigns range. For example: dynamic IP assign range is from 192.168.1.100 ~ 192.168.1.200. 192.168.1.100 will be the Low IP address.
- **High IP Address:** the dynamic IP assign range. High IP address is the end of the dynamic IP assigns range. For example: dynamic IP assign range is from 192.168.1.100 ~ 192.168.1.200. 192.168.1.200 will be the High IP address.
- **Subnet Mask:** the dynamic IP assign range subnet mask.
- **Gateway:** the gateway in your network.
- **DNS:** Domain Name Server IP Address in your network.
- **Lease Time (sec):** It is the time period that system will reset the dynamic IP assignment to ensure the dynamic IP will not been occupied for a long time or the server doesn't know that the dynamic IP is idle.
- And then, click Apply



Figure 3.10: DHCP Server - System Configuration

DHCP Client – System Configuration

When the DHCP server function is active, the system will collect the DHCP client information and displays them here.



Figure 3.11: DHCP Server – Client Entries

DHCP Server - Port and IP Bindings

You can assign a specific IP address, which is the IP in dynamic IP assign range, to the specific port. When a device is connecting to the port and asks for dynamic IP assigning, the system will assign the IP address to the connected device.



Figure 3.12: DHCP Server – Port and IP Binding

TFTP - Update Firmware

Trivial File Transfer Protocol (TFTP) is a very simple file transfer protocol, with the functionality of a very basic form of FTP. It provides the functions to allow the user to update the switch firmware. Before updating, make sure you have your TFTP server ready and the firmware image is on the TFTP server.

- **TFTP Server IP Address:** fill in your TFTP server IP.
- **Firmware File Name:** the name of firmware image.
- And then, click Apply



Figure 3.13: TFTP – Update Firmware

TFTP – Restore Configuration

You can restore Flash ROM value from TFTP server, but you must put the image file on TFTP server first, switch will download back flash image.

- **TFTP Server IP Address:** fill in the TFTP server IP.
- **Restore File Name:** fill in the correct restore file name.
- Click Apply



Figure 3.14: TFTP – Restore Configuration

TFTP - Backup Configuration

You can save current Flash ROM value from the switch to TFTP server, then go to the TFTP restore configuration page to restore the Flash ROM value.

- **TFTP Server IP Address:** fill in the TFTP server IP
- **Backup File Name:** fill the file name
- Click Apply.



Figure 3.15: TFTP – Backup Configuration

System Event Log – Syslog Configuration

Configure the system event mode and system log server IP which you want to collect.

- **Syslog Client Mode:** select the system log mode – client only, server only, or both S/C.
- **System Log Server IP Address:** assign the system log server IP.
- Click Reload to refresh the events log.
- Click Clear to clear all current events log.
- After configuring, Click Apply.



Figure 3.16: Syslog Configuration

System Event Log - SMTP Configuration

You can set up the mail server IP, mail account, account password, and forwarded email account for receiving the event alert.

- **Email Alert:** enable or disable the email alert function.
- **SMTP Server IP:** set up the mail server IP address (when Email Alert enabled, this function will then be available).
- **Sender:** key in a complete email address, e.g. switch101@123.com, to identify where the event log comes from.
- **Authentication:** mark the check box to enable and configure the email account and password for authentication (when Email Alert enabled, this function will then be available).
- **Mail Account:** set up the email account, e.g. johnadmin@123.com, to receive the alert. It must be an existing email account on the mail server, which you had set up in SMTP Server IP Address column.
- **Password:** The email account password.
- **Confirm Password:** reconfirm the password.
- **Rcpt e-mail Address 1 ~ 6:** you can assign up to 6 e-mail accounts also to receive the alert.

- Click Apply.



Figure 3.17: SMTP Configuration

System Event Log - Event Configuration

You can select the 'Syslog' and 'SMTP' events for each port. When selected events occur, the system will send out the log information to the system log server. After configuring, Click Apply.

- **System event selection:** 4 selections – Device cold start, Device warm start, SNMP Authentication Failure, and X-ring topology change. Mark the checkbox to select the event. When selected events occur, the system will issue the logs.
  - **Device cold start:** when the device executes cold start action, the system will issue a log event.
  - **Device warm start:** when the device executes warm start, the system will issue a log event.
  - **Authentication Failure:** when the SNMP authentication fails, the system will issue a log event.
  - **X-ring topology change:** when the X-ring topology has changed, the system will issue a log event.
- **Port event selection:** select the syslog and SMTP events for each port. It has 3 selections—**Link Up**, **Link Down**, and **Link UP & Link Down**. Disable means no event is selected.
  - **Link UP:** the system will issue a log message when port connection links up only.
  - **Link Down:** the system will issue a log message when port connection links down only.
  - **Link UP & Link Down:** the system will issue a log message when port connection is up and down.



Figure 3.18: Event Configuration

Fault Relay Alarm

- **Power Failure:** Mark the check box to enable the function of lighting up FAULT LED on the panel when power fails.
- **Port Link Down/Broken:** Mark the check box to enable the function of lighting up FAULT LED on the panel when ports' states are link-down or broken.



Figure 3.19: Fault Relay Alarm

SNTP Configuration

You can configure the SNTP (Simple Network Time Protocol) settings. The SNTP allows you to synchronize switch clocks on the Internet.

- **SNTP Client:** enable or disable SNTP function to get the time from the SNTP server.
- **Daylight Saving Time:** enable or disable daylight saving time function. When daylight saving time is enabled, you need to configure the daylight saving time period.
- **UTC Timezone:** set the switch location time zone. The following table lists the different location time zone for your reference.

Table 3.18: UTC Timezone

Local Time Zone	Conversion from UTC	Time at 12:00 UTC
November Time Zone	- 1 hour	11am
Oscar Time Zone	-2 hours	10 am
ADT - Atlantic Daylight	-3 hours	9 am
AST - Atlantic Standard EDT - Eastern Daylight	-4 hours	8 am
EST - Eastern Standard CDT - Central Daylight	-5 hours	7 am
CST - Central Standard MDT - Mountain Daylight	-6 hours	6 am

MST - Mountain Standard PDT - Pacific Daylight	-7 hours	5 am
PST - Pacific Standard ADT - Alaskan Daylight	-8 hours	4 am
ALA - Alaskan Standard	-9 hours	3 am
HAW - Hawaiian Standard	-10 hours	2 am
Nome, Alaska	-11 hours	1 am
CET - Central European FWT - French Winter MET - Middle European MEWT - Middle European Winter SWT - Swedish Winter	+1 hour	1 pm
EET - Eastern European, USSR Zone 1	+2 hours	2 pm
BT - Baghdad, USSR Zone 2	+3 hours	3 pm
ZP4 - USSR Zone 3	+4 hours	4 pm
ZP5 - USSR Zone 4	+5 hours	5 pm
ZP6 - USSR Zone 5	+6 hours	6 pm
WAST - West Australian Standard	+7 hours	7 pm
CCT - China Coast, USSR Zone 7	+8 hours	8 pm
JST - Japan Standard, USSR Zone 8	+9 hours	9 pm
EAST - East Australian Standard GST Guam Standard, USSR Zone 9	+10 hours	10 pm
IDLE - International Date Line NZST - New Zealand Standard NZT - New Zealand	+12 hours	Midnight

- **SNTP Sever URL:** set the SNTP server IP address.
- **Daylight Saving Period:** set up the Daylight Saving beginning time and Daylight Saving ending time. Both will be different in every year.
- **Daylight Saving Offset (mins):** set up the offset time.
- **Switch Timer:** Displays the switch current time.
- Click Apply.



Figure 3.20: SNTP Configuration

IP Security

IP security function allows the user to assign 10 specific IP addresses that have permission to access the switch through the web browser for the securing switch management.

- **IP Security Mode:** when this option is in Enable mode, the Enable HTTP Server and Enable Telnet Server check boxes will then be available.
- **Enable HTTP Server:** when this check box is checked, the IP addresses among Security IP1 ~ IP10 will be allowed to access via HTTP service.
- **Enable Telnet Server:** when checked, the IP addresses among Security IP1 ~ IP10 will be allowed to access via telnet service.
- **Security IP 1 ~ 10:** Assign up to 10 specific IP address. Only these 10 IP address can access and manage the switch through the Web browser
- And then, click Apply button to apply the configuration.

Note *Remember to execute the "Save Configuration" action, otherwise the new configuration will lose when switch power off.*



Figure 3.21: IP Security

User Authentication

You can change login user name and password for the management security issue.

- **User name:** Key in the new user name (The default is “admin”)
- **Password:** Key in the new password (The default is “admin”)
- **Confirm password:** Re-type the new password
- And then, click Apply button to apply the configuration.

Figure 3.22: User Authentication

3.2.2 Port

Port setting includes Port Statistics, Port Control, Port Trunk, Port Mirroring, and Rate Limiting. User can use this interface to set the parameters and control the packet flow among the ports.

Port Statistics

The following information provides the current port statistic information.

- **Port:** The port number.
- **Type:** Displays the current speed of connection to the port.
- **Link:** The status of linking—'Up' or 'Down'.
- **State:** It's set by Port Control. When the state is disabled, the port will not transmit or receive any packet.
- **Tx Good Packet:** The counts of transmitting good packets via this port.
- **Tx Bad Packet:** The counts of transmitting bad packets (including undersize [less than 64 bytes], oversize, CRC Align errors, fragments and jabbers packets) via this port.
- **Rx Good Packet:** The counts of receiving good packets via this port.
- **Rx Bad Packet:** The counts of receiving bad packets (including undersize [less than 64 bytes], oversize, CRC error, fragments and jabbers) via this port.
- **Tx Abort Packet:** The aborted packet while transmitting.
- **Packet Collision:** The counts of collision packet.
- **Packet Dropped:** The counts of dropped packet.
- **Rx Bcast Packet:** The counts of broadcast packet.
- **Rx Mcast Packet:** The counts of multicast packet.
- click Apply button to apply the configuration.



Port	Type	Link	State	Tx Good Packet	Tx Bad Packet	Rx Good Packet	Rx Bad Packet	Tx Abort Packet	Packet Collision	Packet Dropped	RX Bcast Packet	RX Mcast Packet
Port.01	100TX	Down	Enable	0	0	0	0	0	0	0	0	0
Port.02	100TX	Down	Enable	0	0	0	0	0	0	0	0	0
Port.03	100TX	Down	Enable	0	0	0	0	0	0	0	0	0
Port.04	100TX	Down	Enable	0	0	0	0	0	0	0	0	0
Port.05	100TX	Down	Enable	0	0	0	0	0	0	0	0	0
Port.06	100TX	Down	Enable	0	0	0	0	0	0	0	0	0
Port.07	100TX	Up	Enable	36098	0	169335	0	0	0	0	76028	17687
Port.08	100TX	Down	Enable	72910	0	108640	0	0	0	0	41	0
Port.09	1GTX/mGBIC	Down	Enable	0	0	0	0	0	0	0	0	0
Port.10	1GTX/mGBIC	Down	Enable	0	0	0	0	0	0	0	0	0

Figure 3.23: Port Statistics

Port Control

In Port Control, you can pull down the selection items to set the parameters of each port to control the transmitting/receiving packets.

- **Port:** select the port that you want to configure.
- **State:** current port status. The port can be set to disable or enable mode. If the port setting is disable then will not receive or transmit any packet.
- **Negotiation:** set auto negotiation status of port.

- **Speed:** set the port link speed.
- **Duplex:** set full-duplex or half-duplex mode of the port.
- **Flow Control:** set flow control function as Enable or Disable in Full Duplex mode. The default value is Enable.
- **Security:** when its state is “On” that means this port accepts only one MAC address.
- Click Apply button to apply the configuration.



Figure 3.24: Port Control

Port Trunk

The Link Aggregation Control Protocol (LACP) provides a standardized means for exchanging information between Partner Systems on a link to allow their Link Aggregation Control instances to reach agreement on the identity of the Link Aggregation Group to which the link belongs, move the link to that Link Aggregation Group, and enable its transmission and reception functions in an orderly manner. Link aggregation lets you group up to 4 ports into one dedicated connections. This feature can expand bandwidth to a device on the network. LACP operation requires full-duplex mode; for more detail information please refers to IEEE 802.3ad.

Aggregator setting

- **System Priority:** a value used to identify the active LACP. The switch with the lowest value has the highest priority and is selected as the active LACP.
- **Group ID:** There are four trunk groups to provide configure. Choose the "Group ID" and click Select.
- **LACP:** If enable, the group is LACP dynamic trunk group. If disable, the group is static trunk group. All ports support LACP dynamic trunk group. If connecting to the device that also supports LACP, the LACP dynamic trunk group will be created automatically.
- **Work ports:** allows max four ports to be aggregated at the same time. With LACP dynamic trunk group, the exceed ports are standby and can be aggregated if work ports fail. If it is static trunk group, the number of ports must be the same as the group member ports.
- Select the ports to join the trunk group. Allows max four ports to be aggregated at the same time. Click Add button to add the port. To remove unwanted ports, select the port and click Remov button.

- If LACP enable, you can configure LACP Active/Passive status in each ports on State Activity page.
- Click Apply.
- Use Apply button to delete Trunk Group. Select the Group ID and click Delete button.



Figure 3.25: Aggregator Setting

Aggregator Information

When you have set up the aggregator setting with LACP disabled, you will see the local static trunk group information here.



Figure 3.26: Aggregator Information

State Activity

When you had set up the LACP aggregator, you can configure port state activity. You can mark or un-mark the port. When you mark the port and click Apply button the port state activity will change to Active. Opposite is Passive.

- **Active:** The port automatically sends LACP protocol packets.
- **Passive:** The port does not automatically send LACP protocol packets, and responds only if it receives LACP protocol packets from the opposite device.

Note *A link having either two active LACP ports or one active port can perform dynamic LACP trunk.*
A link has two passive LACP ports will not perform dynamic LACP trunk because both ports are waiting for an LACP protocol packet from the opposite device.
If you are the active LACP's actor, after you have selected trunk port, the active status will be activated automatically.



Figure 3.27: State Activity

Port Mirroring

The Port mirroring is a method for monitoring traffic in switched networks. Traffic through ports can be monitored by one specific port. That means traffic which goes in or out the monitored (source) ports will be duplicated into the mirror (destination) port.

- **Destination Port:** There is only one port can be selected to be destination (mirror) port for monitoring both RX and TX traffic which come from source port. Or, use one of two ports for monitoring RX traffic only and the other one for TX traffic only. User can connect mirror port to LAN analyzer or Netxray
- **Source Port:** The ports that user wants to monitor. All monitored port traffic will be copied to mirror (destination) port. User can select multiple source ports by checking the RX or TX check boxes to be monitored.
- And then, click Apply button.



Figure 3.28: Port Mirroring

Rate Limiting

You can set up the bandwidth rate and frame limitation type for each port.

- **Ingress Limit Frame type:** select the frame type that wants to filter. The frame types have 4 options for selecting: All, Broadcast/Multicast/Flooded Unicast, Broadcast/Multicast and Broadcast only. Broadcast/Multicast/Flooded Unicast, Broadcast/Multicast and Bbroadcast only types are only for ingress frames. The egress rate only supports All type.

- All the ports support port ingress and egress rate control. For example, assume port 1 is 10Mbps, users can set it's effective egress rate is 1Mbps, ingress rate is 500Kbps. The switch performs the ingress rate by packet counter to meet the specified rate

- **Ingress:** Enter the port effective ingress rate (The default value is "0")
- **Egress:** Enter the port effective egress rate (The default value is "0")
- And then, click Apply to apply the settings



Figure 3.29: Rate Limiting

3.2.3 Protocol

User can set the layer 2 protocol setting via this interface.

VLAN configuration

A Virtual LAN (VLAN) is a logical network grouping that limits the broadcast domain, which would allow you to isolate network traffic, so only the members of the VLAN will receive traffic from the same members of VLAN. Basically, creating a VLAN from a switch is logically equivalent of reconnecting a group of network devices to another Layer 2 switch. However, all the network devices are still plugged into the same switch physically.

The industrial switch supports port-based and 802.1Q (tagged-based) VLAN. The default configuration of VLAN operation mode is "**Disable**".



Figure 3.30: VLAN Configuration

VLAN configuration - Port-based VLAN

Packets can go among only members of the same VLAN group. Note all unselected ports are treated as belonging to another single VLAN. If the port-based VLAN enabled, the VLAN-tagging is ignored.

In order for an end station to send packets to different VLAN groups, it itself has to be either capable of tagging packets it sends with VLAN tags or attached to a VLAN-aware bridge that is capable of classifying and tagging the packet with different VLAN ID based on not only default PVID but also other information about the packet, such as the protocol.



Figure 3.31: Port based mode

- Pull down the select item menu of VLAN Operation Mode, and select Port Based mode.
- Click Add to add a new VLAN group(The maximum VLAN group is up to 256 VLAN groups)
- Entering the VLAN name, group ID and grouping the members of VLAN group
- And then, click Apply



Figure 3.32: Port based mode-Add interface

- You will see the VLAN displays.
- Use Delete button to delete unwanted VLAN.
- Use Edit button to modify existing VLAN group.

Note *Remember to execute the "**Save Configuration**" action, otherwise the new configuration will lose when switch power off.*

802.1Q VLAN

Tagged-based VLAN is an IEEE 802.1Q specification standard. Therefore, it is possible to create a VLAN across devices from different switch venders. IEEE 802.1Q VLAN uses a technique to insert a "tag" into the Ethernet frames. Tag contains a VLAN Identifier (VID) that indicates the VLAN numbers.
You can create Tag-based VLAN, and enable or disable GVRP protocol. There are 256 VLAN groups to provide configure. Enable 802.1Q VLAN, the all ports on the switch belong to default VLAN, VID is 1. The default VLAN can't be deleting.

GVRP allows automatic VLAN configuration between the switch and nodes. If the switch is connected to a device with GVRP enabled, you can send a GVRP request using the VID of a VLAN defined on the switch; the switch will automatically add that device to the existing VLAN.



Figure 3.33: 802.1Q VLAN Configuration

802.1Q Configuration

- Pull down the select item menu of VLAN Operation Mode, and select Port Based mode.
- **Enable GVRP Protocol:** mark the check box to enable GVRP protocol that allows network devices to dynamically exchange VLAN configuration information with other devices. If GVRP protocol is not enabled, user has to set the tagging information manually.
- Select the port that you want to configure.
- **Link Type:** there are 3 types of link type.
    - **Access Link:** single switch only, allow user to group ports by setting the same VID.
    - **Trunk Link:** the extended application of **Access Link**. While the ports are set in this type, they can forward the packets with specified tag among the switches which are included in the same VLAN group.
    - Hybrid Link: Both Access Link and Trunk Link are available.
- **Untagged VID:** assign the untagged frame VID.
- **Tagged VID:** assign the tagged frame VID.
- Click Apply

Group Configuration

Edit the existing VLAN Group.

- Select the VLAN group in the table list.
- Click Apply



Figure 3.34: 802.1Q Group Configuration

- You can Change the VLAN group name and VLAN ID.
- Click Apply.



Figure 3.35: 802.1Q Group Configuration-Edit

Rapid Spanning Tree

The Rapid Spanning Tree Protocol (RSTP) is an evolution of the Spanning Tree Protocol and provides for faster spanning tree convergence after a topology change. The system also supports STP and the system will auto detect the connected device that is running STP or RSTP protocol.

RSTP - System Configuration

- User can view spanning tree information about the Root Bridge
- User can modify RSTP state. After modification, click Apply button
  - **RSTP mode:** user must enable or disable RSTP function before configure the related parameters
  - **Priority (0-61440):** a value used to identify the root bridge. The bridge with the lowest value has the highest priority and is selected as the root. If the value changes, user must reboot the switch. The value must be multiple of 4096 according to the protocol standard rule
  - **Max Age (6-40):** the number of seconds a bridge waits without receiving Spanning-tree Protocol configuration messages before attempting a reconfiguration. Enter a value between 6 through 40
  - **Hello Time (1-10):** the time that controls switch sends out the BPDU packet to check RSTP current status. Enter a value between 1 through 10
  - **Forward Delay Time (4-30):** the number of seconds a port waits before changing from its Rapid Spanning-Tree Protocol learning and listening STP states to the forwarding state. Enter a value between 4 through 30

Note *Follow the rule to configure the MAX Age, Hello Time, and Forward Delay Time.*
2 x (Forward Delay Time value –1) > = Max Age value >= 2 x (Hello Time value +1)



Figure 3.36: RSTP System Configuration interface

RSTP - Port Configuration

You can configure the path cost and priority of each port.

- Select the port in Port column.
- **Path Cost:** The cost of the path to the other bridge from this transmitting bridge at the specified port. Enter a number 1 through 200000000.
- **Priority:** Decide which port should be blocked by priority in LAN. Enter a number 0 through 240. The value of priority must be the multiple of 16.
- **P2P:** Some of the rapid state transactions that are possible within RSTP are dependent upon whether the port concerned can only be connected to exactly one other bridge (i.e. it is served by a point-to-point LAN segment), or can be connected to two or more bridges (i.e. it is served by a shared medium LAN segment). This function allows the P2P status of the link to be manipulated administratively. True is P2P enabling. False is P2P disabling.
- **Edge:** The port directly connected to end stations cannot create bridging loop in the network. To configure the port as an edge port, set the port to "True" status.
- **Non Stp:** The state of whether the port includes the STP mathematic calculation. True is not including STP mathematic calculation. False is including the STP mathematic calculation.
- Click Apply.



Figure 3.37: RSTP Port Configuration interface

SNMP Configuration

Simple Network Management Protocol (SNMP) is the protocol developed to manage nodes (servers, workstations, routers, switches and hubs etc.) on an IP network. SNMP enables network administrators to manage network performance, find and solve network problems, and plan for network growth. Network management systems learn of problems by receiving traps or change notices from network devices implementing SNMP.

System Configuration

Community Strings

You can define new community string set and remove unwanted community string.

- **String:** Fill the name string.
- **RO:** Read only. Enables requests accompanied by this string to display MIB-object information.
- **RW:** Read write. Enables requests accompanied by this string to display MIB-object information and to set MIB objects.
- Click Add.
- To remove the community string, select the community string that you have defined and click Remove. You cannot edit the name of the default community string set.

Agent Mode

Select the SNMP version that you want to use it. And then click Change to switch to the selected SNMP version mode.



Figure 3.38: SNMP System Configuration interface

Trap Configuration

A trap manager is a management station that receives traps, the system alerts generated by the switch. If no trap manager is defined, no traps will issue. Create a trap manager by entering the IP address of the station and a community string. To define management stations as trap manager and enter SNMP community strings and selects the SNMP version.

- **IP Address:** Enter the IP address of trap manager.
- **Community:** Enter the community string.
- **Trap Version:** Select the SNMP trap version type – v1 or v2c.
- Click Add.
- To remove the community string, select the community string that you have defined and click Remove. You cannot edit the name of the default community string set.



Figure 3.39: Trap Configuration interface

SNMPV3 Configuration

Configure the SNMP V3 function.

Context Table

Configure SNMP v3 context table. Assign the context name of context table. Click Add to add context name. Click Remove to remove unwanted context name.

User Profile

Configure SNMP v3 user table..

- **User ID:** set up the user name.
- **Authentication Password:** set up the authentication password.
- **Privacy Password:** set up the private password.
- Click Add to add context name.

- Click Remove to remove unwanted context name.



Figure 3.40: SNMP V3 configuration interface

Group Table

Configure SNMP v3 group table.

- **Security Name (User ID):** Assign the user name that you have set up in user table.
- **Group Name:** Set up the group name.

- Click Add to add context name.
- Click Remove to remove unwanted context name.

Access Table

Configure SNMP v3 access table.

- **Context Prefix:** Set up the context name.
- **Group Name:** Set up the group.
- **Security Level:** Set up the access level.
- **Context Match Rule:** Select the context match rule.
- **Read View Name:** Set up the read view.
- **Write View Name:** Set up the write view.
- **Notify View Name:** Set up the notify view.
- Click Add to add context name.
- Click Remove to remove unwanted context name.

MIBview Table

Configure MIB view table.

- **ViewName:** Set up the name.
- **Sub-Oid Tree:** Fill the Sub OID.
- **Type:** Select the type – exclude or included.
- Click Add to add context name.
- Click Remove to remove unwanted context name.

QoS Configuration

You can configure Qos policy and priority setting, per port priority setting, COS and TOS setting.

QoS Policy and Priority Type

- **Qos Policy:** select the Qos policy rule.
  - Use an 8,4,2,1 weighted fair queuing scheme: The switch will follow 8:4:2:1 rate to process priority queue from High to Lowest queue. For example, as the system processes, 1 frame of the lowest queue, 2 frames of the low queue, 4 frames of the middle queue, and 8 frames of the high queue will be processed at the same time in accordance with the 8,4,2,1 policy rule.
  - Use a strict priority scheme: Always higher queue will be processed first, except higher queue is empty.
- **Priority Type:** there are 5 priority type selections available. Disable means no priority type is selected.
- **Port-base:** the port priority will follow the Port-base that you have assigned – High, middle, low, or lowest.
  - **COS only:** the port priority will only follow the COS priority that you have assigned.
  - **TOS only:** the port priority will only follow the TOS priority that you have assigned.
  - **COS first:** the port priority will follow the COS priority first, and then other priority rule.
  - **TOS first:** the port priority will follow the TOS priority first, and the other priority rule.
- Click Apply.



Figure 3.41: QoS Configuration interface

Port Base Priority

Configure per port priority level.

- **Port 1 ~ Port 10:** each port has 4 priority levels – High, Middle, Low, and Lowest.
- Click Apply.

COS Configuration

Set up the COS priority level.

- **COS priority:** Set up the COS priority level 0~7 –High, Middle, Low, Lowest.
- Click Apply.

TOS Configuration

Set up the TOS priority.

- **TOS priority:** the system provides 0~63 TOS priority level. Each level has 4 types of priority – high, middle, low, and lowest. The default value is "Lowest" priority for each level. When the IP packet is received, the system will check the TOS level value in the IP packet that has received. For example, user set the TOS level 25 is high. The port 1 is following the TOS priority policy only. When the port 1 packet received, the system will check the TOS value of the received IP packet. If the TOS value of received IP packet is 25 (priority = high), and then the packet priority will have highest priority.
- Click Apply.

IGMP Configuration

The Internet Group Management Protocol (IGMP) is a communications protocol used to manage the membership of Internet Protocol multicast groups. IGMP is used by IP hosts and adjacent multicast routers to establish multicast group memberships. It is an integral part of the IP multicast specification, like ICMP for unicast connections. IGMP can be used for online video and gaming, and allows more efficient use of resources when supporting these uses.
IGMP have three fundamental types of message as follows:

Table 3.19: IGMP types

Message	Description
Query	A message sent from the querier (IGMP router or switch) asking for a response from each host belonging to the multicast group.
Report	A message sent by a host to the querier to indicate that the host wants to be or is a member of a given group indicated in the report message.
Leave Group	A message sent by a host to the querier to indicate that the host has quit being a member of a specific multicast group.

The switch support IP multicast, you can enable IGMP protocol on web management's switch setting advanced page, then displays the IGMP snooping information. IP multicast addresses range are from 224.0.0.0 through 239.255.255.255.

- **IGMP Protocol:** Enable or disable the IGMP protocol.
- **IGMP Query:** Select the IGMP query function as Enable or Auto to set the switch as a querier for IGMP version 2 multicast network.
- Click Apply.



Figure 3.42: IGMP Configuration interface

X-Ring

X-Ring provides a faster redundant recovery than Spanning Tree topology. The action is similar to STP or RSTP, but the algorithms not the same.

In the X-Ring topology, every switch should enable X-Ring function and assign two member ports in the ring. Only one switch in the X-Ring group would be set as a master switch, one of its path would be blocked, called backup port, and another port is called working port. Other switches in the X-Ring group are called working switches and their two member ports are called working ports. When the failure of network connection occurs, the backup port will automatically become a working port to recovery the failure.

The switch supports the function and interface for setting the switch as the ring master or slave mode. The ring master can negotiate and place command to other switches in the X-Ring group. If there are 2 or more switches in master mode, then software will select the switch with lowest MAC address number as the ring master. The X-Ring master ring mode will be enabled by the X-Ring configuration interface. Also, user can identify the switch as the ring master from the R.M. LED panel of the LED panel on the switch.

The system also supports the coupling ring that can connect 2 or more X-Ring group for the redundant backup function and dual homing function that prevent connection lose between X-Ring group and upper level/core switch.

- **Enable X-Ring**: To enable the X-Ring function. Marking the check box to enable the X-Ring function.
- **Enable Ring Master**: Mark the check box for enabling this machine to be a ring master.
- **1st & 2nd Ring Ports**: Pull down the selection menu to assign two ports as the member ports. 1st Ring Port is the working port and 2nd Ring Port is the backup port. When 1st Ring Port fails, the system will automatically upgrade the 2nd Ring Port to be the working port.
- **Enable Coupling Ring**: To enable the coupling ring function. Marking the check box to enable the coupling ring function.
- **Coupling port**: Assign the member port.
- **Control port**: Set the switch as the master switch in the coupling ring.
- **Enable Dual Homing**: Set up one of port on the switch to be the Dual Homing port. In an X-Ring group, maximum Dual Homing port is one. Dual Homing only work when the X-Ring function enable.
- And then, click Apply to apply the configuration.

Figure 3.43: X-ring Interface

Note *When the X-Ring function enable, user must disable the RSTP. The X-Ring function and RSTP function cannot exist at the same time.*
Remember to execute the "Save Configuration" action, otherwise the new configuration will lose when switch power off.

3.2.4 Security

In this section, you can configure 802.1x and MAC address table.

802.1X/Radius Configuration

802.1x is an IEEE authentication specification that allows a client to connect to a wireless access point or wired switch but prevents the client from gaining access to the Internet until it provides authority, like a user name and password that are verified by a separate server.

802.1X/Radius - System Configuration

After enabling the IEEE 802.1X function, you can configure the parameters of this function.

- **IEEE 802.1x Protocol:** .enable or disable 802.1x protocol.
- **Radius Server IP:** set the Radius Server IP address.
- **Server Port:** set the UDP destination port for authentication requests to the specified Radius Server.
- **Accounting Port:** set the UDP destination port for accounting requests to the specified Radius Server.
- **Shared Key:** set an encryption key for using during authentication sessions with the specified radius server. This key must match the encryption key used on the Radius Server.
- **NAS, Identifier:** set the identifier for the radius client.
- Click Apply.



Figure 3.44: 802.1x/Radius System Configuration

802.1x/Radius - Port Configuration

You can configure 802.1x authentication state for each port. The State provides Disable, Accept, Reject and Authorize. Use “Space” key change the state value.

- **Reject:** the specified port is required to be held in the unauthorized state.
- **Accept:** the specified port is required to be held in the Authorized state.
- **Authorized:** the specified port is set to the Authorized or Unauthorized state in accordance with the outcome of an authentication exchange between the Supplicant and the authentication server.
- **Disable:** The specified port is required to be held in the Authorized state
- Click Apply.



Figure 3.45: 802.1x/Radius - Port Setting interface

802.1X/Radius - Misc Configuration

- **Quiet Period:** set the period during which the port doesn't try to acquire a supplicant.
- **TX Period:** set the period the port wait for retransmit next EAPOL PDU during an authentication session.
- **Supplicant Timeout:** set the period of time the switch waits for a supplicant response to an EAP request.
- **Server Timeout:** set the period of time the switch waits for a server response to an authentication request.
- **Max Requests:** set the number of authentication that must time-out before authentication fails and the authentication session ends.
- **Reauth period:** set the period of time after which clients connected must be re-authenticated.
- Click Apply.



Figure 3.46: 802.1x/Radius - Misc Configuration

MAC Address Table

Use the MAC address table to ensure the port security.

You can add a static MAC address; it remains in the switch's address table, regardless of whether the device is physically connected to the switch. This saves the switch from having to re-learn a device's MAC address when the disconnected or powered-off device is active on the network again. You can add / modify / delete a static MAC address.

MAC Address Table - Static MAC Address

You can add static MAC address in the switch MAC table here.

- **MAC Address:** Enter the MAC address of the port that should permanently forward traffic, regardless of the device network activity.
- **Port No.:** pull down the selection menu to select the port number.
- Click Add.
- If you want to delete the MAC address from filtering table, select the MAC address and click Delete.



Figure 3.47: Static MAC Addresses interface

MAC Address Table - MAC Filtering

By filtering MAC address, the switch can easily filter pre-configure MAC address and reduce the un-safety. You can add and delete filtering MAC address.



Figure 3.48: MAC Filtering interface

- MAC Address: Enter the MAC address that you want to filter.
- Click Add.
- If you want to delete the MAC address from filtering table, select the MAC address and click Delete.

MAC Address Table - All MAC Addresses

You can view the port of the connected device's MAC address and related devices' MAC address.

- Select the port.
- The selected port of static MAC address information will be displayed here.
- Click Clear MAC Table to clear the current port static MAC address information on screen.



Figure 3.49: All MAC Address interface

Power over Ethernet

This segment shows the Power over Ethernet function.



Figure 3.50: PoE Status

- **Maximum Power Available**: Displays the maximum power supply in Watt.
- **Actual Power Consumption**: This column shows the real-time total power consumption.
- **Main Supply Voltage**: This column shows the output voltage of the system for PoE ports. d means 1/10, and supply 48V when work on PoE situation.
- **Firmware Version**: This column shows the PoE chip's firmware version.
- **Port Knockoff Disabled**: Power Management state where one or more PDs have been powered down so that a higher priority PD may be powered up and yet not exceed the maximum total power available for PDs.
- **AC Disconnect**: Tick this checkbox to monitor the AC impedance on the port terminals and removes power when the impedance rises above a certain value, for a certain period (for details, see the IEEE 802.3af specification).
- **Capacitive Detection**: If the port and capacitive detection are enabled, the capacitances state reads in the voltage result from the constant current. This is then subtracted from the pre-capacitance voltage to get a charge rate. If this charge rate is within the window of the PD signatures, the device is considered to be discovered.
- **Start**: Showing with a tick symbol, the system initializes and resets successfully. And then, click Apply to carry into effect.
- **Port**: The index of PoE ports.
- **Enable State**: Check it to enable the PoE function to the port.
- **Power Limit From Classification**: Check it to decide the power limit method. When this check box is ticked, the system will limit the power supply to the powered device in accordance with the related class.
- **Legacy**: Check it to support the legacy power devices.
- **Priority**: Pull down the selection menu item to choose the priority of power supplying.
- **Port Limit (<15400) mW**: User can key in the power limit value which is under 15.4 Watts.
- **Mode**: Displays the operating mode of the port.
- **Current (mA)**: Displays the operating current of the port.

- **Voltage (V)**: Displays the operating voltage of the port.
- **Power (mW)**: Displays the power consumption of the port.
- **Determined Class**: Displays the PD's class. And then, click Apply to carry into effect.

Factory Default

Reset switch to default configuration. Click Reset to reset all configurations to the default value.



Figure 3.51: Factory Default interface

Save Configuration

Save all configurations that you have made in the system. To ensure the all configuration will be saved. Click Save to save the all configuration to the flash memory.



Figure 3.52: Save Configuration interface

System Reboot



Figure 3.53: System Reboot interface

Reboot the switch in software reset. Click Reboot to reboot the system.

CHAPTER 4

Troubleshooting

Chapter 4 Troubleshooting

Verify that is using the right power cord/adapter (+12~48V_{DC}), please don't use the power adaptor with DC output voltage higher than 48 V, or it will burn this converter down.

Select the proper UTP cable to construct user network. Please check that is using the right cable. Use Unshielded Twisted-Pair (UTP) or Shielded Twisted-Pair (STP) cable for RJ-45 connections: 100 Category 3, 4 or 5 cable for 10 Mbps connections or 100 Category 5 cable for 100 Mbps connections. Also, be sure that the length of any twisted-pair connection does not exceed 100 meters (328 feet).

Diagnosing LED Indicators

The switch can be easily monitored through panel indicators, which describes common problems user may encounter and where user can find possible solutions, to assist in identifying.

If the power indicator does not light up when the power cord is plugged in, user may have a problem with power cord. Then check for loose power connections, power losses or surges at power outlet. If user still cannot resolve the problem, contact the local dealer for assistance.

If the Industrial switch LED indicators are normal and the connected cables are correct but the packets still cannot transmit, please check your system's Ethernet devices configuration or status.

APPENDIX A

Pin Assignment & Wiring

Appendix A Pin Assignment & Wiring

It is suggested to adopt ELA/TIA as the wiring of the RJ-45.



Figure A.1: RJ-45 Pin Assignment



Figure A.2: EIA/TIA-568B



Figure A.3: EIA/TIA-568A



DB 9-pin Female

Figure A.4: DB 9-pin female connector

DB9 Connector	RJ-45 Connector
NC	1 Orange/White
2	2 Orange
3	3 Green/White
NC	4 Blue
5	5 Blue/White
NC	6 Green
NC	7 Brown/White
NC	8 Brown

APPENDIX B

Compatible SFP Modules

Appendix B Compatible SFP Modules

The table below shows compatible SFP modules for EKI-7659CPI.

Item	Brand	Part Number	Mode	Transmission Distance
1	AVAGO	AFBR-5710PZ	Multi-mode	550m
2	APAC	LM28-C3S-TC-N		550m
3	HOATECH	HTI8512-X5ATO		550m
4	SPACE SHUTTLE	S56L-S85-6L-N		550m
5	LuminentOIC	SP-GB-LX	Single-mode	10km
		SP-GB-ELX		20km
		SP-GB-XD		50km
6	AVAGO	AFCT-5710PZ		10km
7	APAC	LS38-C3M-TC-N		20km
8	SPACE SHUTTLE	S56L-L13-6L-N		10km